Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-905-2875

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

0.906 inches

#### Terminal Length:

0.172 inches

Body Diameter:

0.781 inches

### Shaft Diameter:

0.125 inches

### Shaft Length:

### 0.500 inches

## Mounting Bushing Length:

0.375 inches

### **Body Length:**

0.406 inches

## **Overall Diameter:**

0.952 inches

## Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Screw Thread Diameter:

0.250 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## **Mounting Method:**

Locking bushing

## **Electrical Resistance Per Section:**

10.0 kilohms single section

## Power Dissipation Rating Per Section In Watts:

0.3 free air single section

# Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section



## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0