Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-905-2876

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Body Diameter:**

0.781 inches

### Shaft Diameter:

0.125 inches

#### Shaft Length:

0.500 inches

Mounting Bushing Length:

0.375 inches

### Body Length:

### 0.406 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Screw Thread Diameter:

0.250 inches

## Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

### **Terminal Location:**

Radially positioned over less than half the circumference

### Mounting Method:

Locking bushing

#### **Features Provided:**

Shaft locking device

### **Electrical Resistance Per Section:**

5.0 kilohms single section

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

## Power Dissipation Rating Per Section In Watts:

0.3 free air single section

### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section



Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0