NSN 5905-00-905-5268

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



0-905-5268

View Online at https://aerobasegroup.com/nsn/5905-00).
Section Quantity:	
Body Style:	
Rectangular w/mounting holes/slots	
Reliability Indicator:	
Not established	
Overall Length:	
Between 1.300 inches and 1.340 inches	
Terminal Length:	
0.500 inches	
Overall Height:	
Between 0.769 inches and 0.861 inches	
Overall Width:	
Between 0.180 inches and 0.200 inches	
Mounting Hole Diameter:	
Between 0.088 inches and 0.098 inches	
Shaft Diameter:	
Between 0.100 inches and 0.130 inches	
Shaft Length:	
Between 0.060 inches and 0.080 inches	
Body Length:	
Between 1.240 inches and 1.260 inches	
Body Width:	
Between 0.180 inches and 0.200 inches	
Body Height:	
Between 0.300 inches and 0.330 inches	
Shaft Style:	
Round, slotted	
Contact Arm Electrical Off Position:	
Fully ccw	
Actuator Type:	
Single shaft	
Center To Center Distance Between Terminals:	
0.900 inches	
Lateral Distance Between Mounting Hole Centers:	
1.000 inches	
Mounting Facility Quantity:	
2	
Terminal Location:	
Lower adjacent side single row	

Mounting Method:

Unthreaded hole

NSN 5905-00-905-5268

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
20.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 6120.0 and 9720.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.700 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-27208 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 pin
Specification Data:
81349-mil-r-27208/8 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No