

View Online at <https://aerobasegroup.com/nsn/5905-00-905-5302>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Overall Length:

1.000 inches

First Flat Length:

Between 0.344 inches and 0.375 inches

Flat Height:

Between 0.078 inches and 0.100 inches

Shaft Diameter:

0.1248 inches

Shaft Length:

0.500 inches

Body Length:

1.250 inches

Body Width:

0.250 inches

Body Height:

0.315 inches

Overall Diameter:

1.281 inches

Shaft Style:

Round, flatted

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 75.0 and 77.0

Maximum Starting Torque:

1.00 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Nonturn Device Radius:

0.500 inches

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Screw Thread Diameter:

0.112 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

40.0

Mounting Facility Quantity:

3

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 75.0 and 77.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

65.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0