Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-905-9341

## Section Quantity: 1 Shaft Style: Round Actuator Type: Double ended shaft Effective Electrical Rotation In Deg Angular Rotation: 1080.0 Maximum Starting Torque: 1.50 inch-ounces Maximum Running Torque: 1.00 inch-ounces **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 50.000 ohms single section **Rotary Actuator Travel In Angular Deg:** 1080.0 **Function Conformity Tolerance Per Section:** -0.10/+0.10 single section **Power Dissipation Rating Per Section In Watts:** 3.0 free air single section **Function Conformity Per Section:** Single section zero based linearity **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section **Terminal Type And Quantity:** 3 turret Shelf Life: N/a

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0