NSN 5905-00-905-9351

Section Quantity:

Reliability Indicator:

Rectangular w/mounting holes/slots

Body Style:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-905-9351

Not established
Terminal Length:
Between 0.469 inches and 0.531 inches
Mounting Hole Diameter:
Between 0.088 inches and 0.098 inches
Shaft Diameter:
Between 0.120 inches and 0.130 inches
Shaft Length:
Between 0.040 inches and 0.060 inches
Body Length:
Between 1.234 inches and 1.266 inches
Body Width:
Between 0.283 inches and 0.297 inches
Body Height:
Between 0.328 inches and 0.359 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 9360.0 and 10080.0
Maximum Starting Torque:
8.00 inch-ounces
Maximum Running Torque:
8.00 inch-ounces
Center To Center Distance Between Terminals:
Between 0.695 inches and 0.705 inches
Fragility Factor:
Moderately rugged
Lateral Distance Between Mounting Hole Centers:
Between 0.995 inches and 1.005 inches
Mounting Facility Quantity:
2
Terminal Location:

Lower adjacent side two rows

NSN 5905-00-905-9351

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Terminal and unthreaded hole
Center To Center Distance Between Terminal Rows:
Between 0.095 inches and 0.105 inches
Features Provided:
Humidity proof
Cubic Measure:
0.125 cubic inches
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 9360.0 and 10080.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.295 inches and 0.305 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0