Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-907-2018

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.250 inches

#### Shaft Diameter:

0.130 inches

#### Shaft Length:

0.250 inches

#### Mounting Bushing Length:

0.190 inches

### Body Length:

## 0.335 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

360.0

#### Screw Thread Diameter:

0.138 inches

## Screw Thread Series Designator:

Unf

#### Screw Thready Qty Per Inch (tpi):

40.0

#### **Terminal Location:**

Rear end

#### **Mounting Method:**

Standard bushing

#### **Electrical Resistance Per Section:**

50.0 ohms single section

## Rotary Actuator Travel In Angular Deg:

360.0

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

## **Power Dissipation Rating Per Section In Watts:**

0.25 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

# NSN 5905-00-907-2018

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



#### **Actuator Travel Control Feature:**

Continuous motion

#### Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0