

View Online at <https://aerobasegroup.com/nsn/5905-00-907-2019>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.7510 inches

Pilot Length:

0.0600 inches

Undercut Diameter:

0.750 inches

Undercut Width:

0.0580 inches

Body Diameter:

0.876 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.436 inches

Body Length:

0.758 inches

Mounting Lip Diameter:

0.8760 inches

Mounting Lip Depth:

0.0640 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Fragility Factor:

Moderately rugged

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Features Provided:

Humidity proof

Electrical Resistance Per Section:

1.160 kilohms single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0