## NSN 5905-00-907-3414

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-907-3414

Ozatlan Ozantitu
Section Quantity:
Overall Length:
2.125 inches
Overall Height:
2.125 inches
Overall Width:
1.750 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.531 inches
Mounting Bushing Length:
0.250 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
3.00 inch-ounces
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
5.000 kilohms single section
Function Conformity Tolerance Per Section:
-0.05/+0.05 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Resistance Tolerance Per Section In Percent:
2.0/.2.0 single costion

-3.0/+3.0 single section

## NSN 5905-00-907-3414

Precision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature in Deg Ceisius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:

3 solder stud

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0