

View Online at https://aerobasegroup.com/nsn/5905-00-907-5070

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.3750 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

0.375 inches

Undercut Width:

0.0620 inches

Body Diameter:

0.500 inches

Shaft Diameter:

onan Diameter.

0.093 inches

Shaft Length:

0.313 inches

Body Length:

1.118 inches

Mounting Lip Diameter:

0.5000 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

0.25 inch-ounces

Maximum Running Torque:

0.02 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.003 inches



Lateral Runout: 0.003 inches **Pilot Diameter Runout:** 0.002 inches **Shaft Radial Play:** 0.002 inches **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 2.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.25/+0.25 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Clutch **Function Characteristic Per Section:** Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0