NSN 5905-00-908-5376

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-908-5376
Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Body Diameter:
0.813 inches
Body Length:
0.391 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
270.0
Terminal Location:
Rear end
Mounting Method:
Flange
Electrical Resistance Per Section:
25.0 ohms single section
Rotary Actuator Travel In Angular Deg:
270.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-908-5376

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0