NSN 5905-00-908-5414

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-908-5414

Onesting Occupation
Section Quantity:
Body Style:
Rectangular
Reliability Indicator:
Not established
Overall Length:
0.500 inches
Overall Height:
1.125 inches
Overall Width:
0.820 inches
Body Length:
0.500 inches
Body Width:
0.820 inches
Body Height:
1.125 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
240.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Terminal
Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:
240.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
1.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

NSN 5905-00-908-5414

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
A single section
Precious Material And Location:
Terminals silver
Precious Material:
Silver
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0