## NSN 5905-00-908-5433

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-908-5433 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Body Length:** 0.380 inches **Body Width:** 0.907 inches **Body Height:** 0.925 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 290.0 **Terminal Location:** Lower adjacent side single row **Mounting Method: Terminal Electrical Resistance Per Section:** 2.5 megohms single section **Rotary Actuator Travel In Angular Deg:** 290.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5905-00-908-5433

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



_		••	• •					
וו	em	ш	112	r17	2+	$\sim$	n	
$\boldsymbol{-}$	CIII	••	ıιa	114	.aı	ı		

No

Fiig:

A002a0