## NSN 5905-00-908-7235

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-908-7235 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Body Length:** 0.380 inches **Body Width:** 0.907 inches **Body Height:** 0.925 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 290.0 **Center To Center Distance Between Terminals:** 0.179 inches **Mounting Facility Quantity: Terminal Location:** Dual inline **Mounting Method:** Tab **Electrical Resistance Per Section:** 5.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 290.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.344 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -30.0/+30.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** 

70.0 single section

Standard Taper Curve Per Se
A single section

Terminal Type And Quantity:
3 wire lead

## NSN 5905-00-908-7235

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0