NSN 5905-00-909-4101

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-909-4101

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|-------------------------------------------------------------------------------------------------------------------------------------------|
| -260.0/+260.0 |
| Electrical Resistance: |
| 30.000 kilohms |
| Resistance Tolerance In Percent: |
| -5.000/+5.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 25.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 350.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+350.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Type: |
| Tab w/wire lead |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.500 inches |
| Body Diameter: |
| 0.406 inches |
| Body Length: |
| 1.750 inches |
| Power Dissipation Rating In Watts: |
| 10.000 free air |
| Terminal Width: |
| 0.188 inches |
| End Application: |
| Virginia class cgn (41), nimitz class cvn, forrestal class cv, kilauea class t-ae 26, austin ship class lpd-4 amphibious transport docks. |
| General purpose electronic test equipment (gpete). F-4 simulator. |
| Criticality Code Justification: |
| Feat |
| Special Features: |
| Weapon system essential |
| Style Designator: |
| Radial terminal each end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

No

Demilitarization:

NSN 5905-00-909-4101

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0