NSN 5905-00-910-5700

Section Quantity:

Cylindrical bushing mounted

Between 1.213 inches and 1.437 inches

Reliability Indicator:

Not established

Overall Length:

Terminal Length: 0.484 inches Body Diameter:

Body Style:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-910-5700

•
1.281 inches
Shaft Diameter:
Between 0.248 inches and 0.252 inches
Shaft Length:
Between 0.094 inches and 0.156 inches
Mounting Bushing Length:
Between 0.469 inches and 0.531 inches
Body Length:
0.750 inches
Overall Diameter:
1.766 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Front end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section

NSN 5905-00-910-5700

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:		
40.0 single section		
Standard Taper Curve Per Section:		
A single section		
Ferminal Type And Quantity:		
3 tab, solder lug		
Shelf Life:		
N/a		
Unit Of Measure:		
Demilitarization:		