## NSN 5905-00-910-9416

**Section Quantity:** 

Cylindrical bushing mounted

Between 1.563 inches and 1.687 inches

Reliability Indicator:

Not established

Overall Length:

**Terminal Length:** 0.437 inches

**Body Style:** 

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-910-9416

Body Diameter:
1.750 inches
Shaft Diameter:
Between 0.094 inches and 0.156 inches
Shaft Length:
Between 0.248 inches and 0.252 inches
Mounting Bushing Length:
Between 0.469 inches and 0.531 inches
Body Length:
1.000 inches
Overall Diameter:
2.187 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Front end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
5.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section

## NSN 5905-00-910-9416

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

**Demilitarization:** No

Fiig:

A002a0