

View Online at <https://aerobasegroup.com/nsn/5905-00-911-3975>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**liilength:**

Between 1.157 inches and 1.281 inches

**Terminal Length:**

Between 0.125 inches and 0.197 inches

**Body Diameter:**

Between 0.844 inches and 0.906 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

0.147 inches

**Mounting Bushing Length:**

Between 0.375 inches and 0.437 inches

**Body Length:**

Between 0.657 inches and 0.719 inches

**liidiameter:**

Between 0.960 inches and 1.084 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 6 oclock

**Nonturn Device Radius:**

0.250 inches

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

1.0 ohms single section

**Rotary Actuator Travel In Angular Deg:**

300.0

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-200.0 to 200.0 single section

**Power Dissipation Rating Per Section In Watts:**

12.5 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

**Actuator Travel Control Feature:**

Stops

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0