

View Online at <https://aerobasegroup.com/nsn/5905-00-911-3975>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

liilength:

Between 1.157 inches and 1.281 inches

Terminal Length:

Between 0.125 inches and 0.197 inches

Body Diameter:

Between 0.844 inches and 0.906 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.147 inches

Mounting Bushing Length:

Between 0.375 inches and 0.437 inches

Body Length:

Between 0.657 inches and 0.719 inches

liidiameter:

Between 0.960 inches and 1.084 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

0.250 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

1.0 ohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-200.0 to 200.0 single section

Power Dissipation Rating Per Section In Watts:

12.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0