## NSN 5905-00-911-4367

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-911-4367 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.9690 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 0.975 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 1.062 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.500 inches **Body Length:** 0.688 inches **Mounting Lip Diameter:** 1.0620 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Maximum Starting Torque:** 1.00 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Shaft End Play:** 0.003 inches

**Shaft Runout:** 0.001 inches



NSN 5905-00-911-4367 Precision Nonwire Wound Variable Resistor - Page 2 of 3	Aei
Lateral Runout:	
0.001 inches	
Pilot Diameter Runout:	
0.001 inches	
Shaft Radial Play:	
0.001 inches	
Mechanical Backlash In Deg Angular Rotation:	
0.1	
Terminal Location:	
Radially positioned over more than half the circumference	
Mounting Method:	
Clamp ring	
Electrical Resistance Per Section:	
10.0 kilohms single section	
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:	
10.2 single section	
Rotary Actuator Travel In Angular Deg:	
360.0	
Function Conformity Tolerance Per Section:	
-0.10/+0.10 single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
125.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
-100.0/+100.0 single section	
Power Dissipation Rating Per Section In Watts:	
0.022 free air single section	
Function Conformity Per Section:	
Single section absolute linearity	
Fixed Tap Quantity Per Section:	
2 single section	

**Tap Location Tolerance Per Section:** 

-1.0/+1.0 degrees angular rotation single section

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

**Actuator Travel Control Feature:** 

Continuous motion

**Function Characteristic Per Section:** 

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

**Terminal Type And Quantity:** 

5 turret

Shelf Life:

N/a

## NSN 5905-00-911-4367

Precision Nonwire Wound Variable Resistor - Page 3 of 3



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0