Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-911-4367

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.9690 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

0.975 inches

Undercut Width:

0.0620 inches

Body Diameter:

1.062 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.500 inches

Body Length:

0.688 inches

Mounting Lip Diameter:

1.0620 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Maximum Starting Torque:

1.00 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Shaft End Play:

0.003 inches

Shaft Runout:

0.001 inches

NSN 5905-00-911-4367

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Lateral Runout:	
0.001 inches	
Pilot Diameter Runout:	
0.001 inches	
Shaft Radial Play:	
0.001 inches	
Mechanical Backlash In Deg Angular Rotation:	
0.1	
Terminal Location:	
Radially positioned over more than half the circumference	
Mounting Method:	
Clamp ring	
Electrical Resistance Per Section:	
10.0 kilohms single section	
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:	
10.2 single section	
Rotary Actuator Travel In Angular Deg:	
360.0	
Function Conformity Tolerance Per Section:	
-0.10/+0.10 single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
125.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
-100.0/+100.0 single section	
Power Dissipation Rating Per Section In Watts:	
0.022 free air single section	
Function Conformity Per Section:	
Single section absolute linearity	
Fixed Tap Quantity Per Section:	
2 single section	
Tap Location Tolerance Per Section:	
-1.0/+1.0 degrees angular rotation single section	
Resistance Tolerance Per Section In Percent:	
-5.0/+5.0 single section	
Actuator Travel Control Feature:	
Continuous motion	
Function Characteristic Per Section:	
Single section linear	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
55.0 single section	
Terminal Type And Quantity:	
5 turret	
Shelf Life:	

N/a

NSN 5905-00-911-4367

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0