Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-911-8830

Section Quantity:

2

Body Style:

Cylindrical hole/slot mounted

Reliability Indicator:

Not established

Overall Length:

6.250 inches

First Flat Length:

1.562 inches

Flat Height:

0.344 inches

Body Diameter:

8.000 inches

Shaft Diameter:

0.375 inches

Shaft Length:

2.000 inches

Body Length:

4.250 inches

Overall Diameter:

9.250 inches

Mounting Hole/stud Circle Diameter:

3.000 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

320.0

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

20.0

Mounting Facility Quantity:

2

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

NSN 5905-00-911-8830

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section: 1.0 ohms all sections **Rotary Actuator Travel In Angular Deg:** 320.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 all sections **Power Dissipation Rating Per Section In Watts:** 500.0 free air all sections **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 all sections **Actuator Travel Control Feature:** Stops Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections **Standard Taper Curve Per Section:** A all sections **Terminal Type And Quantity:** 6 tab, solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0