## NSN 5905-00-912-2241

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-912-2241

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.8750 inches
Pilot Length:
0.0620 inches
Overall Length:
Between 2.171 inches and 2.225 inches
Undercut Diameter:
Between 0.874 inches and 0.875 inches
Undercut Width:
0.0620 inches
Body Diameter:
1.172 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Body Length:
Between 1.563 inches and 1.583 inches
Overall Diameter:
1.000 inches
Mounting Lip Diameter:
1.0000 inches
Mounting Lip Depth:
0.0680 inches
Shaft Style:
Round
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 3600.0 and 3604.0
Maximum Starting Torque:
0.40 inch-ounces
Maximum Running Torque:

0.30 inch-ounces

## NSN 5905-00-912-2241

Precision Wire Wound Variable Resistor - Page 2 of 3



Maximum Stop Torque:
100.00 inch-ounces
Shaft End Play:
0.005 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.001 inches
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 3604.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

-

## NSN 5905-00-912-2241

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0