NSN 5905-00-912-2836

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-912-2836 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.75000 inches Pilot Length: Between 0.05700 inches and 0.06700 inches **Overall Length:** 1.387 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** Between 0.05700 inches and 0.06700 inches **Body Diameter:** Between 0.870 inches and 0.880 inches **Shaft Diameter:** Between 0.120 inches and 0.130 inches **Shaft Length:** Between 0.469 inches and 0.531 inches **Body Length:** 0.781 inches **Overall Diameter:** 1.281 inches **Mounting Lip Diameter:** Between 0.87000 inches and 0.88000 inches **Mounting Lip Depth:** Between 0.05700 inches and 0.06700 inches **Shaft Style:** Round **Actuator Type:** Double ended shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:** 0.40 inch-ounces **Terminal Location:**

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

NSN 5905-00-912-2836

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
20.0 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
175.0 single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
1.2 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Tap Location From Ccw Terminal Per Section In Ohms:
10000.0 single section
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
20.0 single section
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A002a0