## NSN 5905-00-912-2889



Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-00-912-2889 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.156 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.375 inches

**Body Length:** 0.625 inches

**Shaft Style:** 

Round, slotted

**Actuator Type:** 

Single shaft

**Nonturn Device Location:** 

At 9 oclock

**Nonturn Device Radius:** 

0.531 inches

**Screw Thread Diameter:** 

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Locking bushing

**Electrical Resistance Per Section:** 

250.0 kilohms single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

**Power Dissipation Rating Per Section In Watts:** 

2.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-20.0/+20.0 single section

## NSN 5905-00-912-2889

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a

Demilitarization:

**Unit Of Measure:** 

No

Fiig:

A002a0