## NSN 5905-00-912-6433

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-912-6433 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.6245 inches and 0.6250 inches Pilot Length: Between 0.0570 inches and 0.0670 inches **Overall Length:** 1.611 inches **Undercut Diameter:** Between 0.651 inches and 0.661 inches **Undercut Width:** 0.0570 inches **Body Diameter:** Between 0.745 inches and 0.775 inches **Shaft Diameter:** Between 0.124 inches and 0.125 inches **Shaft Length:** 0.375 inches **Body Length:** Between 1.145 inches and 1.155 inches **Mounting Lip Diameter:** Between 0.7450 inches and 0.7550 inches **Mounting Lip Depth:** Between 0.0570 inches and 0.0670 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 352.0 **Maximum Starting Torque:** 0.20 inch-ounces **Maximum Running Torque:** 

0.20 inch-ounces

**Shaft Runout:** 

0.001 inches

## NSN 5905-00-912-6433

Precision Wire Wound Variable Resistor - Page 2 of 3



Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
500.0 ohms c and better industrial clears
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
40.4 2nd section and 80.8 2nd section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.35/+0.35 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 all sections
Power Dissipation Rating Per Section In Watts:
0.5 free air all sections
Function Conformity Per Section:
All sections independent linearity
Fixed Tap Quantity Per Section:
2 2nd section
Tap Location Tolerance Per Section:
-1.0/+1.0 degrees angular rotation all sections
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
100.0 all sections
Terminal Type And Quantity:
10 turret
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

No

## NSN 5905-00-912-6433

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0