NSN 5905-00-912-9332

Section Quantity:

Reliability Indicator:

Not established

Rectangular w/mounting holes/slots

Body Style:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-912-9332

Overall Length:
1.060 inches
Terminal Length:
Between 0.185 inches and 0.215 inches
Overall Height:
0.560 inches
Mounting Hole Diameter:
0.088 inches
Shaft Diameter:
Between 0.090 inches and 0.110 inches
Shaft Length:
Between 0.050 inches and 0.070 inches
Body Length:
Between 0.985 inches and 1.015 inches
Body Width:
Between 0.270 inches and 0.290 inches
Body Height:
Between 0.350 inches and 0.370 inches
Shaft Style:
Shaft Style: Round, slotted
Round, slotted
Round, slotted Actuator Type:
Round, slotted Actuator Type: Single shaft
Round, slotted Actuator Type: Single shaft Center To Center Distance Between Terminals:
Round, slotted Actuator Type: Single shaft Center To Center Distance Between Terminals: Between 0.490 inches and 0.510 inches
Round, slotted Actuator Type: Single shaft Center To Center Distance Between Terminals: Between 0.490 inches and 0.510 inches Lateral Distance Between Mounting Hole Centers:
Round, slotted Actuator Type: Single shaft Center To Center Distance Between Terminals: Between 0.490 inches and 0.510 inches Lateral Distance Between Mounting Hole Centers: Between 0.825 inches and 0.835 inches
Round, slotted Actuator Type: Single shaft Center To Center Distance Between Terminals: Between 0.490 inches and 0.510 inches Lateral Distance Between Mounting Hole Centers: Between 0.825 inches and 0.835 inches Mounting Facility Quantity:
Round, slotted Actuator Type: Single shaft Center To Center Distance Between Terminals: Between 0.490 inches and 0.510 inches Lateral Distance Between Mounting Hole Centers: Between 0.825 inches and 0.835 inches Mounting Facility Quantity: 2
Round, slotted Actuator Type: Single shaft Center To Center Distance Between Terminals: Between 0.490 inches and 0.510 inches Lateral Distance Between Mounting Hole Centers: Between 0.825 inches and 0.835 inches Mounting Facility Quantity: 2 Terminal Location:
Round, slotted Actuator Type: Single shaft Center To Center Distance Between Terminals: Between 0.490 inches and 0.510 inches Lateral Distance Between Mounting Hole Centers: Between 0.825 inches and 0.835 inches Mounting Facility Quantity: 2 Terminal Location: Lower adjacent side single row
Round, slotted Actuator Type: Single shaft Center To Center Distance Between Terminals: Between 0.490 inches and 0.510 inches Lateral Distance Between Mounting Hole Centers: Between 0.825 inches and 0.835 inches Mounting Facility Quantity: 2 Terminal Location: Lower adjacent side single row Mounting Method:
Round, slotted Actuator Type: Single shaft Center To Center Distance Between Terminals: Between 0.490 inches and 0.510 inches Lateral Distance Between Mounting Hole Centers: Between 0.825 inches and 0.835 inches Mounting Facility Quantity: 2 Terminal Location: Lower adjacent side single row Mounting Method: Unthreaded hole
Round, slotted Actuator Type: Single shaft Center To Center Distance Between Terminals: Between 0.490 inches and 0.510 inches Lateral Distance Between Mounting Hole Centers: Between 0.825 inches and 0.835 inches Mounting Facility Quantity: 2 Terminal Location: Lower adjacent side single row Mounting Method: Unthreaded hole Center To Center Distance Between Terminal Rows:

NSN 5905-00-912-9332

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
5400.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
0.2 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Clutch
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0