Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-913-1793

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** Between 0.515 inches and 0.555 inches **Terminal Length:** 6.000 inches **Overall Height:** Between 0.490 inches and 0.510 inches **Overall Width:** Between 0.182 inches and 0.197 inches **Mounting Hole Diameter:** Between 0.090 inches and 0.098 inches Shaft Diameter: Between 0.058 inches and 0.098 inches Shaft Length: Between 0.025 inches and 0.045 inches **Body Length:** Between 0.490 inches and 0.510 inches **Body Width:** Between 0.182 inches and 0.197 inches **Body Height:** Between 0.490 inches and 0.510 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 7200.0 and 16200.0 Maximum Starting Torque: 5.00 inch-ounces Lateral Distance Between Mounting Hole Centers: Between 0.513 inches and 0.526 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** 

Unthreaded hole

NSN 5905-00-913-1793 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
100.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 7200.0 and 16200.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-600.0/+600.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0