## NSN 5905-00-913-2173

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-913-2173

Electrical Resistance: 453.000 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.190 inches Power Dissipation Rating In Watts: 0.050 free air Criticality Code Justification: Tost Style Designator: Axial terminal each end Test Data Document: 94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Lite: N/a Unit of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: -1.000/4-1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0/-4145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.045 inches Body Length: 0.190 inches Power Dissipation Rating in Watts: 0.050 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Tests Data Document: 94756-443-9561 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	-50.0/+50.0
Resistance Tolerance in Percent: -1.000/41.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.045 inches Body Length: 0.190 inches Power Dissipation Rating in Watts: 0.050 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: N/a Unit Of Measure: Demilitarization:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.045 inches Body Length: 0.190 inches Power Dissipation Rating In Watts: 0.500 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	453.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.045 inches Body Length: 0.190 inches Power Dissipation Rating In Watts: 0.050 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Na Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0/+145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.045 inches  Body Length: 0.190 inches  Power Dissipation Rating In Watts: 0.050 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0/+145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.045 inches  Body Length:  0.190 inches  Power Dissipation Rating In Watts:  0.050 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.045 inches Body Length: 0.190 inches Power Dissipation Rating In Watts: 0.050 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	100.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.045 inches Body Length: 0.190 inches Power Dissipation Rating In Watts: 0.050 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.045 inches Body Length: 0.190 inches Power Dissipation Rating In Watts: 0.505 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	150.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.045 inches Body Length: 0.190 inches Power Dissipation Rating In Watts: 0.050 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.045 inches Body Length: 0.190 inches Power Dissipation Rating In Watts: 0.050 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	-65.0/+145.0
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.045 inches  Body Length: 0.190 inches  Power Dissipation Rating In Watts: 0.050 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.045 inches  Body Length: 0.190 inches  Power Dissipation Rating In Watts: 0.050 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Encapsulated
Reliability Indicator:  Not established  Body Diameter: 0.045 inches  Body Length: 0.190 inches  Power Dissipation Rating In Watts: 0.050 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document: 94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Terminal Type:
Not established  Body Diameter:  0.045 inches  Body Length: 0.190 inches  Power Dissipation Rating In Watts: 0.050 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Wire lead
Body Diameter:  0.045 inches  Body Length: 0.190 inches  Power Dissipation Rating In Watts: 0.050 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Reliability Indicator:
0.045 inches  Body Length: 0.190 inches  Power Dissipation Rating In Watts: 0.050 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Not established
Body Length:  0.190 inches  Power Dissipation Rating In Watts: 0.050 free air  Criticality Code Justification: Test  Style Designator:  Axial terminal each end  Test Data Document: 94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Body Diameter:
0.190 inches  Power Dissipation Rating In Watts: 0.050 free air  Criticality Code Justification: Test  Style Designator:  Axial terminal each end  Test Data Document: 94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	0.045 inches
Power Dissipation Rating In Watts:  0.050 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Body Length:
Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	0.190 inches
Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure: Demilitarization:	Power Dissipation Rating In Watts:
Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	0.050 free air
Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Criticality Code Justification:
Axial terminal each end  Test Data Document:  94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Test
Test Data Document:  94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Style Designator:
94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	94756-443-0951 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a Unit Of Measure: Demilitarization:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure:  Demilitarization:	Shelf Life:
 Demilitarization:	N/a
	Unit Of Measure:
	<del></del>
No	Demilitarization:
	No
Fiig:	Fiig:
A001a0	A001a0