Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-913-2954

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** Between 1.300 inches and 1.340 inches **Terminal Length:** Between 0.469 inches and 0.531 inches **Overall Height:** Between 0.800 inches and 0.861 inches **Overall Width:** Between 0.180 inches and 0.200 inches **Mounting Hole Diameter:** Between 0.088 inches and 0.098 inches Shaft Diameter: Between 0.100 inches and 0.130 inches Shaft Length: Between 0.060 inches and 0.080 inches **Body Length:** Between 1.240 inches and 1.260 inches **Body Width:** Between 0.180 inches and 0.200 inches **Body Height:** Between 0.300 inches and 0.330 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 6120.0 and 9720.0 Maximum Starting Torque: 8.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.890 inches and 0.910 inches Lateral Distance Between Mounting Hole Centers: Between 0.995 inches and 1.005 inches **Mounting Facility Quantity:** 2 **Terminal Location:**

Lower adjacent side single row

NSN 5905-00-913-2954 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Manuating Mathedu
Mounting Method:
Terminal and unthreaded hole
Electrical Resistance Per Section:
100.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 6120.0 and 9720.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.690 inches and 0.710 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-600.0/+600.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0