## NSN 5905-00-913-4325

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-913-4325

Electrical Resistance: 13.700 kilohms Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: -0.067 inches Body Length: -0.325 inches Power Dissipation Rating In Watts: -0.100 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
13.700 kilohms Resistance Tolerance in Percent: -1.000/-1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: -100.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: -150.0 -1	-50.0/+50.0
Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.067 inches Body Length: 0.325 inches Power Dissipation Rating in Watts: 0.100 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: No. Unit Of Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 100.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.0467 inches Body Length: 0.325 inches Power Dissipation Rating In Watts: 0.100 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit of Measure: - Demilitarization: No	13.700 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  100.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0/+145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.067 inches  Body Length:  0.325 inches  Power Dissipation Rating in Watts:  0.100 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-9052 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Sheff Life:  No  Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0/+145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Note established  Body Diameter:  0.067 inches  Body Length:  0.325 inches  Power Dissipation Rating in Watts:  0.100 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0/+145.0  Inclosure Method:  Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.067 inches  Body Length: 0.325 inches  Power Dissipation Rating In Watts: 0.100 free air  Criticality Code Justification: Test: Style Designator: Axial terminal each end  Test Data Document: 94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.04-145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.067 inches Body Length: 0.325 inches Power Dissipation Rating In Watts: 0.100 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	100.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.067 inches Body Length: 0.325 inches Power Dissipation Rating In Watts: 0.100 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.087 inches Body Length: 0.325 inches Power Dissipation Rating In Watts: 0.100 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	150.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.067 inches Body Length: 0.325 inches Power Dissipation Rating In Watts: 0.100 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.067 inches Body Length: 0.325 inches Power Dissipation Rating In Watts: 0.100 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-9052 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	-65.0/+145.0
Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.067 inches  Body Length: 0.325 inches  Power Dissipation Rating In Watts: 0.100 free air  Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.067 inches  Body Length: 0.325 inches  Power Dissipation Rating In Watts: 0.100 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No	Encapsulated
Reliability Indicator: Note established  Body Diameter: 0.067 inches  Body Length: 0.325 inches  Power Dissipation Rating In Watts: 0.100 free air  Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure: Demilitarization: No	Terminal Type:
Note established  Body Diameter:  0.067 inches  Body Length: 0.325 inches  Power Dissipation Rating In Watts: 0.100 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No	Wire lead
Body Diameter:  0.067 inches  Body Length:  0.325 inches  Power Dissipation Rating In Watts:  0.100 free air  Criticality Code Justification: Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No	Reliability Indicator:
Body Length:  0.325 inches  Power Dissipation Rating In Watts: 0.100 free air  Criticality Code Justification: Test  Style Designator:  Axial terminal each end  Test Data Document: 94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Not established
Body Length:  0.325 inches  Power Dissipation Rating In Watts: 0.100 free air  Criticality Code Justification: Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Body Diameter:
0.325 inches  Power Dissipation Rating In Watts: 0.100 free air  Criticality Code Justification: Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	0.067 inches
Power Dissipation Rating In Watts:  0.100 free air  Criticality Code Justification: Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Body Length:
O.100 free air  Criticality Code Justification: Test  Style Designator:  Axial terminal each end  Test Data Document: 94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	0.325 inches
Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document:  94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	Power Dissipation Rating In Watts:
Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	0.100 free air
Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Criticality Code Justification:
Axial terminal each end  Test Data Document:  94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Test
Test Data Document:  94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Style Designator:
94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	94756-443-0952 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a Unit Of Measure:  Demilitarization: No	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No	Shelf Life:
 Demilitarization: No	N/a
No	Unit Of Measure:
No	<del></del>
	Demilitarization:
Eiia.	No
riig.	Fiig:
A001a0	A001a0