## NSN 5905-00-913-4999

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-913-4999 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established liilength: 1.776 inches **Terminal Length:** 1.500 inches **Body Diameter:** 0.345 inches **Body Length:** 0.276 inches liidiameter: 0.345 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Rear end **Mounting Method: Terminal Features Provided:** Humidity proof **Electrical Resistance Per Section:** 50.000 ohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

## NSN 5905-00-913-4999

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Actuator Travel Control Feature:                                    |
|---|
| Continuous motion   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 50.0 single section   |
| Terminal Type And Quantity:   |
| 3 pin   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |