## NSN 5905-00-913-5108

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-913-5108

-20.0/+20.0 Electrical Resistance: 7.900 kilohms Resistance Tolerance in Percent: -0.010/40.010 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating in Watts: 0.125 free air Criticality Code Justification: Test Sylve Designator: Axial terminal each end Test Data Document: 94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: Demilitarization: No Filig: A001a0	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: -0.010/40,010 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.04-125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0853-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	
Resistance Tolerance In Percent: -0.010/+0.010 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure:	Electrical Resistance:
-0.010/4-0.010 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/±125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.350 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Na Unit Of Measure:	7.900 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 947756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Na Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/4125.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-9053-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:  — Demilitarization: No Filg:	-0.010/+0.010
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead Reliability Indicator: Not established  Body Diameter: 0.250 inches  Body Length: 0.340 inches  Power Dissipation Rating in Watts: 0.125 free air Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 94756-443-9053-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-56.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	150.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure: Demilitarization: No Fig:	-55.0/+125.0
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter: 0.250 inches  Body Length: 0.340 inches  Power Dissipation Rating In Watts: 0.125 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Flig:	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Body Diameter: 0.250 inches  Body Length: 0.340 inches  Power Dissipation Rating In Watts: 0.125 free air  Criticality Code Justification: Test  Style Designator: Axial terminal each end Test Data Document: 94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Encapsulated
Reliability Indicator: Not established  Body Diameter: 0.250 inches  Body Length: 0.340 inches  Power Dissipation Rating In Watts: 0.125 free air  Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note established  Body Diameter: 0.250 inches  Body Length: 0.340 inches  Power Dissipation Rating In Watts: 0.125 free air  Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Wire lead
Body Diameter:  0.250 inches  Body Length:  0.340 inches  Power Dissipation Rating In Watts:  0.125 free air  Criticality Code Justification: Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Reliability Indicator:
Body Length:  0.340 inches  Power Dissipation Rating In Watts:  0.125 free air  Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document:  94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Not established
Body Length:  0.340 inches  Power Dissipation Rating In Watts: 0.125 free air  Criticality Code Justification: Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Body Diameter:
0.340 inches  Power Dissipation Rating In Watts: 0.125 free air  Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	0.250 inches
Power Dissipation Rating In Watts:  0.125 free air  Criticality Code Justification: Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Body Length:
0.125 free air  Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	0.340 inches
Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.125 free air
Style Designator: Axial terminal each end Test Data Document: 94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Criticality Code Justification:
Axial terminal each end  Test Data Document:  94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test
Test Data Document: 94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	94756-443-0953-428 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
N/a Unit Of Measure: Demilitarization: No Fiig:	etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No  Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0