NSN 5905-00-913-6331

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-913-6331

0.00.00
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.437 inches
Body Diameter:
Between 1.046 inches and 1.078 inches
Shaft Diameter:
Between 0.248 inches and 0.250 inches
Shaft Length:
1.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
Between 0.531 inches and 0.593 inches
Overall Diameter:
1.406 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
Between 0.515 inches and 0.547 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.2 megohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section

2.0 free air single section

NSN 5905-00-913-6331

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



R	esistance	Tolerance	Per 9	Section	In	Percent:
◥	esisiance	i olei alice	rei .	Section		reiteiit.

-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0