NSN 5905-00-913-8369

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-913-8369

Silectrical Resistance: 125.000 ohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 15.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 15.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 15.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 15.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Inclosure Method: Incl	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 1.000/4-1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Range Of Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Range Of Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Range Of Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Range Of Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Range Of Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Range Of Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Range Of Tempurature	-30.0/+30.0
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 15.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+275.0 Tempurature Range Of Tempuratur	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0/+275.0 Inclosure Method: Incapsulated Terminal Type: Write lead Reliability Indicator: Not established 30dy Diameter: 1.004 inches 30dy Length: 1.0406 inches 20dy Length: 1.0406 inches 20dy Length: 2.0406 inches 20dy Length: 2.0416 inches 20dy Length: 20dy Leng	825.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established 300y Diameter: 1.004 inches 300y Length: 1.406 inches 300y Length: 1.406 inches 300 ree air Style Designator: 2014 Style Designator: 2024 Style Designator: 2024 Style Postignation (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Schelf Life: 1.406 1.501 1.502 1.503 1.50	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.094 inches Body Length: 10.406 inches Power Dissipation Rating In Watts: 10.406 inches Power Dissipation Rating In Watts: 10.406 inches 10.406 i	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 1.094 inches Body Length: 1.406 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 11349-milr26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Wa Juit Of Measure: Demilitarization:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Prempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Ferminal Type: Wife lead Reliability Indicator: Not established Body Diameter: 1.0.094 inches Body Diameter: 1.0.095 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Avial terminal each end Fest Data Document: 191349-milr26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Juit Of Measure: Demilitarization:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Body Diameter: 10.094 inches Body Diameter: 10.095 inches Power Dissipation Rating In Watts: 10.000 free air Style Designator: Exist Erminal each end Test Data Document: 10.1349-miliz6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: 10.00 Measure: 10.00 Measur	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established 3ody Diameter: .0.094 inches 3ody Length: .0.406 inches Power Dissipation Rating In Watts: .0.000 free air Style Designator: xistal terminal each end Fest Data Document: 11349-milt26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ***, etc.). Shelf Life: Via Unit Of Measure: - Demilitarization:	275.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Exial terminal each end Fest Data Document: 101349-milir26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Jinit Of Measure: - Demilitarization: No	-55.0/+275.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document: 181349-milr26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Va Juit Of Measure: Demilitarization:	Inclosure Method:
Wire lead Reliability Indicator: Not established Reliability Indicator: Not established Reliability Indicator: Not established Reliability Indicator: Note stablished Reliability Indicator: Note and Indicator: Note Body Length: Note Indicator Indicator Responding Indicator Respondin	Encapsulated
Reliability Indicator: Not established Body Diameter: D.094 inches Body Length: D.406 inches Power Dissipation Rating In Watts: D.400 free air Style Designator: Exital terminal each end Fest Data Document: D1349-milr26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization:	Terminal Type:
Note established Body Diameter: D.094 inches Body Length: D.406 inches Power Dissipation Rating In Watts: D.000 free air Style Designator: Axial terminal each end Fest Data Document: B1349-milr26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization:	Wire lead
Body Length: 0.406 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Unit Of Measure:	Reliability Indicator:
Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.000 free air Style Designator: Axial terminal each end Fest Data Document: 0.81349-milr26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization:	Not established
Body Length: 0.406 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization:	Body Diameter:
Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 31349-milr26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization:	0.094 inches
Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document: 131349-milr26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Body Length:
Style Designator: Axial terminal each end Fest Data Document: B1349-milr26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	0.406 inches
Axial terminal each end Fest Data Document: 81349-milr26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Power Dissipation Rating In Watts:
Axial terminal each end Fest Data Document: 31349-milr26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	1.000 free air
Test Data Document: 81349-milr26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). 8helf Life: 1/4 1/2 1/4 1/5 1/6 1/6 1/6 1/6 1/6 1/6 1/7 1/7	Style Designator:
B1349-milr26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization:	81349-milr26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Shelf Life: N/a Unit Of Measure: - Demilitarization:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Jnit Of Measure: - Demilitarization:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: - Demilitarization:	Shelf Life:
- Demilitarization:	N/a
No	Unit Of Measure:
No	
	Demilitarization:
Filg:	No
	Fiig:
N001a0	A001a0