## NSN 5905-00-913-8564

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-913-8564

Section Quantity:				
1				
Body Style:				
Cylindrical bushing mounted				
Reliability Indicator:				
Not established				
Overall Length:				
1.469 inches				
Body Diameter:				
0.938 inches				
Shaft Diameter:				
0.250 inches				
Shaft Length:				
0.875 inches				
Mounting Bushing Length:				
0.375 inches				
Body Length:				
0.594 inches				
Overall Diameter:				
1.250 inches				
Shaft Style:				
Round				
Actuator Type:				
Single shaft				
Nonturn Device Location:				
At 9 oclock				
Nonturn Device Radius:				
0.437 inches				
Screw Thread Diameter:				
0.375 inches				
Screw Thread Series Designator:				
Unef				
Screw Thready Qty Per Inch (tpi):				
32.0				
Terminal Location:				
Radially positioned over less than half the circumference				
Mounting Method:				
Standard bushing				
Electrical Resistance Per Section:				
25.0 kilohms single section				
Power Dissipation Rating Per Section In Watts:				

5.0 free air single section

## NSN 5905-00-913-8564

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance	l olerance Per	Section	In Percent
-10.0/+10.0 s	ingle section		

-

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0