

View Online at <https://aerobasegroup.com/nsn/5905-00-914-0132>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

2.094 inches

**Body Diameter:**

1.156 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.625 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

1.266 inches

**Overall Diameter:**

1.482 inches

**Shaft Style:**

Round, slotted

**Switch Type:**

Rotary

**Switch Voltage Rating In Volts:**

250.0

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

333.0

**Switch Operating Position:**

Start of rotation

**Switch Contact Arrangement:**

Double pole, single throw, normally closed

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear-bottom

**Mounting Method:**

Standard bushing

**Features Provided:**

Switch

**Electrical Resistance Per Section:**

250.000 ohms all sections

**Rotary Actuator Travel In Angular Deg:**

333.0

**Resistance Temperature Characteristic Range Per Section In Percent:**

+0.0/+4.5 -55 degrees celsius all sections and +0.0/+2.5 -25 degrees celsius all sections and +0.0/+1.5 0 degrees celsius all sections and  
-1.5/+1.5 85 degrees celsius all sections and +0.0/+3.5 120 degrees celsius all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

120.0 all sections

**Power Dissipation Rating Per Section In Watts:**

1.0 free air all sections

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 all sections

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 all sections

**Switch Current Type And Rating In Amps:**

1.000 ac/dc

**Standard Taper Curve Per Section:**

A all sections

**Terminal Type And Quantity:**

10 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0