## NSN 5905-00-914-0876

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-914-0876

Section Quantity:

**Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** 0.450 inches **Mounting Hole Diameter:** 0.078 inches **Shaft Diameter:** 0.093 inches Shaft Length: 0.075 inches **Body Length:** 0.375 inches **Body Width:** 0.185 inches **Body Height:** 0.375 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Lateral Distance Between Mounting Hole Centers:** 0.375 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end

**Mounting Method:**Unthreaded hole

Features Provided:

r cataroo i rovia

Humidity proof

**Electrical Resistance Per Section:** 

5.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

9000 0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

## NSN 5905-00-914-0876

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:** No