

View Online at <https://aerobasegroup.com/nsn/5905-00-914-1488>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.090 mils and 0.096 centimeters

Shaft Diameter:

Between 0.060 inches and 0.065 inches

Shaft Length:

0.030 inches

Body Length:

Between 0.492 inches and 0.508 inches

Body Width:

Between 0.182 inches and 0.197 inches

Body Height:

Between 0.492 inches and 0.508 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

15120.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Lateral Distance Between Mounting Hole Centers:

Between 0.515 inches and 0.525 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Features Provided:

Humidity proof

Cubic Measure:

0.047 cubic inches

Electrical Resistance Per Section:

500.0 ohms c and better flooring

Rotary Actuator Travel In Angular Deg:

15120.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 7th secondary quality

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0