NSN 5905-00-914-2429

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-914-2429 **Section Quantity:** 2 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.053 inches **Body Length:** 1.250 inches **Body Width:** 0.500 inches **Body Height:** 0.312 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Maximum Starting Torque:** 7.50 inch-ounces **Maximum Running Torque:** 7.50 inch-ounces **Maximum Stop Torque:** 20.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 50.0 kilohms all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

135.0 all sections

NSN 5905-00-914-2429

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coe	fficient Of Resistand	ce Per Section II	n Ppm Per D	eg Celsius:
-----------------	-----------------------	-------------------	-------------	-------------

-50.0/+50.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A002a0