

View Online at <https://aerobasegroup.com/nsn/5905-00-914-6313>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Overall Length:

Between 1.182 inches and 1.192 inches

Terminal Length:

0.392 inches

Body Diameter:

Between 1.030 inches and 1.150 inches

Shaft Diameter:

Between 0.248 inches and 0.251 inches

Shaft Length:

0.620 inches

Body Length:

Between 0.470 inches and 0.650 inches

Overall Diameter:

1.180 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.516 inches and 0.546 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

Electrical Resistance Per Section:

50.000 kilohms single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

0.500 inch long bushing

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0