## NSN 5905-00-914-6313

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-914-6313

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Overall Length:
Between 1.182 inches and 1.192 inches
Terminal Length:
0.392 inches
Body Diameter:
Between 1.030 inches and 1.150 inches
Shaft Diameter:
Between 0.248 inches and 0.251 inches
Shaft Length:
0.620 inches
Body Length:
Between 0.470 inches and 0.650 inches
Overall Diameter:
1.180 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
Between 0.516 inches and 0.546 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Locking bushing
Electrical Resistance Per Section:
50.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

## NSN 5905-00-914-6313

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



<b>Standard Taper Curve Per Section:</b>
A single section
Special Features:
0.500 inch long bushing
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0