NSN 5905-00-914-6444

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-914-6444 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.3120 inches and 1.3125 inches Pilot Length: 0.0620 inches **Overall Length:** 0.965 inches **Undercut Diameter:** 1.285 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 1.437 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.485 inches **Body Length:** 0.962 inches **Overall Diameter:** 1.437 inches **Mounting Lip Diameter:** 1.4370 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 354.0 **Maximum Starting Torque:**

Maximum Starting Torque:
0.60 inch-ounces
Maximum Running Torque:
0.40 inch-ounces

NSN 5905-00-914-6444

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.00250 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.00150 inches
Shaft Radial Play:
0.004 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
1.000 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
68.0 single section and 133.5 single section and 172.65 single section and 177.0 single section and 181.35 single section and 220.5 single
section and 286.0 single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.30/+0.30 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
7 single section
Tap Location Tolerance Per Section:
-1.0/+1.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

10 turret

70.0 single section

Terminal Type And Quantity:

NSN 5905-00-914-6444

Precision Wire Wound Variable Resistor - Page 3 of 3



Sneit	Lite:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0