## NSN 5905-00-914-8628

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-914-8628

**Section Quantity:** 

1

**Body Style:** 

Rectangular w/mounting holes/slots

**Reliability Indicator:** 

Not established

**Overall Length:** 

Between 1.254 inches and 1.359 inches

**Terminal Length:** 

Between 0.469 inches and 0.624 inches

**Overall Height:** 

Between 0.235 inches and 0.300 inches

**Overall Width:** 

Between 0.235 inches and 0.300 inches

**Mounting Hole Diameter:** 

Between 0.088 inches and 0.098 inches

**Shaft Diameter:** 

Between 0.100 inches and 0.140 inches

**Shaft Length:** 

Between 0.036 inches and 0.077 inches

**Body Length:** 

Between 1.218 inches and 1.282 inches

**Body Width:** 

Between 0.235 inches and 0.300 inches

**Body Height:** 

Between 0.235 inches and 0.300 inches

Shaft Style:

Round, slotted

**Actuator Type:** 

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:** 

Between 6120.0 and 9720.0

**Maximum Starting Torque:** 

8.00 inch-ounces

**Center To Center Distance Between Terminals:** 

Between 0.490 inches and 0.510 inches

**Lateral Distance Between Mounting Hole Centers:** 

Between 0.109 inches and 0.160 inches

**Mounting Facility Quantity:** 

2

**Terminal Location:** 

Radially positioned over less than half the circumference

## NSN 5905-00-914-8628

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:	
Unthreaded hole	
Center To Center Distance Between Terminal Rows:	
0.100 inches	
Electrical Resistance Per Section:	
1.000 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
Between 6120.0 and 9720.0	
Center To Center Distance Between Center Terminal And Outside Terminal:	
0.300 inches	
Resistance Tempurature Characteristic Range Per Section In Percent:	
+0.0/+5.5 -55 degrees celsius single section and +0.0/+3.0 -25 degrees celsius single section and -2.0/+2.0 85 degrees ce	elsius single
section and -5.0/+5.0 125 degrees celsius single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
125.0 single section	
Power Dissipation Rating Per Section In Watts:	
0.25 free air single section	
Resistance Tolerance Per Section In Percent:	
-10.0/+10.0 single section	
Actuator Travel Control Feature:	
Clutch	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 pin	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	