## NSN 5905-00-914-9225

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-914-9225

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -20.0/+20.0  Electrical Resistance: 52.200 kilohms  Resistance Tolerance In Percent: -0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
52.200 kilohms  Resistance Tolerance In Percent: -0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0
Resistance Tolerance In Percent: -0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0
-0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0
125.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
145.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-65.0/+145.0
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Reliability Indicator:
Not established
Body Diameter:
0.250 inches
Body Length:
0.312 inches
Power Dissipation Rating In Watts:
0.125 free air
Style Designator:
Axial terminals one end
Test Data Document:
81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A001a0