Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-915-1216

Section Quantity:
1
Reliability Indicator:
Not established
Shaft Diameter:
0.250 inches
Shaft Length:
1.000 inches
Mounting Bushing Length:
0.375 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
10.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Fixed Tap Quantity Per Section:
1 single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Tap Location From Ccw Terminal Per Section In Ohms:
5000.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0