## NSN 5905-00-916-3627

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-916-3627 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Body Length:** 0.875 inches **Body Width:** 1.750 inches **Body Height:** 2.500 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 240.0 **Terminal Location:** Lower adjacent side single row **Mounting Method:** Tab **Electrical Resistance Per Section:** 1.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 240.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Continuous motion Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug

N/a

Shelf Life:

## NSN 5905-00-916-3627

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0