Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5905-00-917-3465

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

## **Reliability Indicator:**

Not established

## Mounting Hole Diameter:

0.087 inches

#### Shaft Diameter:

0.125 inches

- Shaft Length:
- 0.063 inches

Body Length:

#### 1.250 inches

Body Width:

## 0.250 inches

**Body Height:** 

0.328 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

9000.0

## Lateral Distance Between Mounting Hole Centers:

1.000 inches

## **Mounting Facility Quantity:**

2

## Terminal Location:

Rear end

#### **Mounting Method:**

Unthreaded hole

#### **Features Provided:**

Humidity proof

## **Electrical Resistance Per Section:**

50.0 kilohms single section

## **Rotary Actuator Travel In Angular Deg:**

9000.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

200.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

# NSN 5905-00-917-3465

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

5.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

# Actuator Travel Control Feature:

Clutch

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

## Fiig:

A002a0