NSN 5905-00-917-5073

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-917-5073

Section Quantity: 1 Body Style: Rectangular w/mounting holes Reliability Indicator: Not established Mounting Hole Diameter: 0.093 inches
Body Style: Rectangular w/mounting holes Reliability Indicator: Not established Mounting Hole Diameter:
Rectangular w/mounting holes Reliability Indicator: Not established Mounting Hole Diameter:
Reliability Indicator: Not established Mounting Hole Diameter:
Not established Mounting Hole Diameter:
Mounting Hole Diameter:
-
Shaft Diameter:
0.060 inches
Shaft Length:
0.030 inches
Body Length: 0.500 inches
Body Width: 0.187 inches
Body Height: 0.500 inches
Shaft Style: Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
15120.0
Lateral Distance Between Mounting Hole Centers:
0.520 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Features Provided:
Humidity proof
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
15120.0
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

NSN 5905-00-917-5073

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No