

View Online at <https://aerobasegroup.com/nsn/5905-00-917-7310>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Pilot Diameter:**

Between 0.96830 inches and 0.96880 inches and 0.49950 inches and 0.50000 inches

**Pilot Length:**

Between 0.05200 inches and 0.07200 inches and 0.05200 inches and 0.07200 inches

**Overall Length:**

2.575 inches

**Undercut Diameter:**

Between 0.959 inches and 0.965 inches

**Undercut Width:**

Between 0.05200 inches and 0.07200 inches

**Body Diameter:**

1.072 inches

**Shaft Diameter:**

Between 0.1244 inches and 0.1249 inches

**Shaft Length:**

Between 0.590 inches and 0.650 inches

**Body Length:**

1.925 inches

**Overall Diameter:**

1.072 inches

**Mounting Lip Diameter:**

1.06200 inches

**Mounting Lip Depth:**

Between 0.05200 inches and 0.07200 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

3600.0

**Maximum Starting Torque:**

0.75 inch-ounces

**Shaft End Play:**

0.00500 inches

**Shaft Runout:**

0.001 inches

**Shaft Radial Play:**

0.001 inches

**Terminal Location:**

Rear end

**Mounting Method:**

Clamp ring

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.05/+0.05 single section

**Function Conformity Per Section:**

Single section terminal base linearity

**Fixed Tap Quantity Per Section:**

1 single section

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

Single section linear

**Special Features:**

10 ohms maximum output impedance, 3000 ohms min input impedance

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0